



EVO-SAFE SERIES

BURGLAR & FIRE RESISTANT SAFE









Digital Lock



Time Lock (available in 2 or 3 movements)



Digital Lock



Keyless Combination Lock (available in 3 or 4 wheel)






Front Trap



Internal Drawers -Refer Representative For Drawer Configuration



Gun Racks with Ammunition Stroage Compartment



	EXTERNAL (IIIII)			@90°	@ 180°	THE CONTRACT				
MODEL	(H)	(w)	(D)	(D+P)	(OD)	(ow)	(h)	(had)	(w)	(d)
OKEV-1	710 (28")	648 (25.5")	680 (26.8")	730 (28.7")	1255 (51.2")	1170 (46.1")	500 (19.7")	375 (14.8")	438 (17.2")	410 [16.2"]
OKEV-2	900 (35.5")	648 (25.5")	724 (28.5")	774 (30.5")	1305 (51.4")	1165 (45.9")	698 (27.4")	547 (21.5")	438 (17.2")	454 [17.9"]
OKEV-3	1105 (43.5")	724 (28.5")	775 (30.5")	825 (32.5")	1430 (56.3")	1320 (52")	895 (35.2")	726 (28.6")	514 (20.2")	505 (19.9")
OKEV-4	1422 (56")	762 (30")	813 (32")	863 (34")	1500 (59")	1395 (55")	1212 (47.7")	1037 (40.8")	552 (21.7")	543 (21.4")
OKEV-5GT	1702 (67")	762 (30")	813 (32")	863 (34")	1500 (59")	1395 (55")	1490 (58.7")	1290 (50.8")	550 (21.6")	535 (21.1")
OKEV-6GT	1829 (72")	762 (30")	813 (32")	863 (34")	1500 (59")	1395 (55")	1617 (63.7")	1417 (55.8")	550 (21.6")	535 (21.1")

INTERNAL: (h) — height / (w) — width / (d) — depth / (had) — height above drawer

SIZE	STANDARD FITTINGS	APPROXIMATE NETT WEIGHT	PACKING CASE SIZE	GROSS WEIGHT
OKEV-1	1 full width drawer 1 adjustable shelf 3 moving bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	620kgs	910mm x 810mm x 900mm	660kgs
OKEV-2	1 full width drawer 1 adjustable shelf 4 moving bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	823kgs	1100mm x 810mm x 900mm	863kgs
OKEV-3	1 full width drawer 1 adjustable shelf 4 moving front bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	1104kgs	1310mm x 900mm x 1000mm	1154kgs
OKEV-4	1 full width drawer 2 adjustable shelves 5 moving front bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	1468kgs	1620mm x 930mm x 1000mm	1538kgs
OKEV-5GT	1 full width drawer 3 adjustable shelves 6 moving front bolts 1 vertical rebate 2 top moving bolt 2 bottom moving bolts	1780kgs	1900mm x 930mm x 1050mm	1860kgs
OKEV-6GT	1 full width drawer 3 adjustable shelves 6 moving front bolts 1 vertical rebate 2 top moving bolt 2 bottom moving bolts	1900kgs	2050mm x 950mm x 1050mm	1980kgs

NOTE: Maximum permissible deviation is ±10% for weight
In the interest of our clents, certain details concerning the protective features of MOEM EVO Series safes have not been disclosed in this brochure.
Such information can however be obtained by consulting your MOEM representatives.

NOTE: As our policy is one of consistent improvement, we reserve the right to alter any part of this specifications without notice and without incurring any obligation.


AvanGuard SERIES


BURGLAR & FIRE RESISTANT SAFE





AVANGUARD SERIES SPECIFICATIONS





SIZE	STANDARD FITTINGS	APPROXIMATE NETT WEIGHT	PACKING CASE SIZE	GROSS WEIGHT
OKAV-1	1 full width drawer 1 adjustable shelf 3 moving bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	563kgs	910mm x 810mm x 900mm	603kgs
OKAV-2	1 full width drawer 1 adjustable shelf 4 moving bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	743kgs	1100mm x 810mm x 900mm	783kgs
OKAV-3	1 full width drawer 1 adjustable shelf 4 moving front bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	1013kgs	1310mm x 900mm x 1000mm	1063kgs
OKAV-4	1 full width drawer 2 adjustable shelves 5 moving front bolts 1 vertical rebate 1 top moving bolt 1 bottom moving bolt	1338kgs	1620mm x 930mm x 1000mm	1408kgs
OKAV-5GT	1 full width drawer 3 adjustable shelves 6 moving front bolts 1 vertical rebate 2 top moving bolt 2 bottom moving bolts	1611kgs	1900mm x 930mm x 1050mm	1691kgs
OKAV-6GT	1 full width drawer 3 adjustable shelves 6 moving front bolts 1 vertical rebate 2 top moving bolt 2 bottom moving bolts	1714kgs	2050mm x 950mm x 1050mm	1794kgs

NOTE: As our policy is one of consistent improvement, we reserve the right to alter any part of this specifications without notice and without incurring any obligation.

24 HOURS DEPOSITORY SYSTEM


DEPOSITORY SYSTEM (DRAWER TRAP SYSTEM)

Drawer trap system allows deposit of cash and documents without having to open the main safe door. System is fitted with an anti-fishing plate to deter fishing of content from the safe. Drawer trap is also lockable. Model AV-1, AV-2 and AV-3 can be fitted with depository system (drawer trap).

FRONT DRAWER TRAP




CROSS-SECTION - FRONT DRAWER TRAP



BACK DRAWER TRAP



CROSS-SECTION -BACK DRAWER TRAP



- 915mmH x 648mmW x 730mmD
- 1105mmH x 648mmW x 774mmD
- 1307mmH x 724mmW x 825mmD

- * Exclusion from SP certification.
- * Back Drawer Trap (Refer Representative for Detailed Drawings).

INTERNAL FITTINGS

- * Safe Fitted with Internal Drawers Various Sizes, Compartments and Combinations Available (Refer Representatives)
- * Safe for Armoury (Refer Representative)

SAFE FITTED WITH INTERNAL DRAWERS



SAFE FOR ARMOURY





FEATURES

The overall thickness of door measures 100mm with an effective specially formulated thermo-alloy MT metal-mix barrier material protective thickness of 50mm. The design form an integral part of the door structure strength together with locking mechanism. The overall thickness of body measures 65mm encased with MOEM specially formulated thermo-alloy MT metal-mix barrier material composite.

BOLT-WORK & LOCKING MECHANISM

Compact series safe is designed with a 3 way running bolt-work locking system. The door is further secured by full vertical interlocking system. Bolt measures 25mm in diameter.

Compact series safe comes complete with 3 wheel keyless combination lock (1,000,000 combination variation) and a key lock. Other locking options such as digital lock available as accessories. (optional).

INTERNAL FITTINGS


Compact series safe comes complete with one adjustable steel

shelf. Model MS200, MS300 and MS300T comes complete with a lockable internal bottom drawer.

Door Protective Thickness 50mm

FIRE RESISTANCE
Safe is tested for 30 minutes in accordance to JIS 1037:1989 (Japanese Industrial Standard). (*refer test report)

Body Protective Thickness 65mm	
Thermo-Alloy MT Metal-Mix Barrier Material	
3-Way Running Bolt	
Internal Fittings	
Fire Resistance	



	EXTE	RNAL (mm	and inches	1	D00R @90°	DOOR @ 180°	IN	TERN.	AL (m	nm)	WEIGHT
MODEL	(H)	(w)	(D)	(D+P)	(OD)	(ow)	(h)	(had)	(w)	(d)	(KGS)
OKMS100	385 (15.2")	533 (21")	457 (18")	502	920	970	245	-	393	270	170
OKMS200	584 (23")	508 (20")	533 (21")	578	985	925	445	318	368	360	250
OKMS300	685 (27")	508 (20")	533 (21")	578	985	925	545	420	368	360	285
OKMS100T	508 (20")	533 (21")	457 (18")	502	920	970	245	200	393	270	210
OKMS300T	813 (32.1")	508 (20")	533 (21")	578	985	925	545	395	368	360	330

INTERNAL: (h) — height / (w) — width / (d) — depth / (had) — height above drawer




MS100T & MS300T [DRAWER TRAP SYSTEM]
Drawer trap system allows deposit of cash and documents without having to open the main safe door. System is fitted with an anti-fishing plate to deter fishing of content from the safe. Drawer trap is also lockable. These features are ideally suited for retailers i.e kiosks, gasoline stations, restaurants, mini-marts and others where there is turnover of employee shifts and cash turnover.

ACCESSORIES


Digital lock / Envelope slot / *Other special fittings Standard colour: Light Grey

- Safe comes complete with 1 adjustable shelf MS200, MS300 & MS300T come complete with internal drawer Ensure door able to open 180° to maximize usage & drawer usage Recommended to allow 25mm gap on each side Internal height MS100T & MS300T is measured up to anti-fishing plate D+P-Overall depth + handle OD-Overall depth door @90° OW-Overall width door @180°

- OW-Overall width door @180 °
 Had-Height above drawer *except MS100T
 Floor bolting to be specified before manufacturing
 Measurement in inches ["] as guide
 Weight ±10%













Model	External Dimension	Weight
OKFRC 2 (2 drawers)	826mmH x 530mmW x 770mmD	192Kgs
OKFRC 3 (3 drawers)	1188mmH x 530mmW x 770mmD	260Kgs
OKFRC 4 (4 drawers)	1550mmH x 530mmW x 770mmD	360Kgs
	Internal Dimension	
Drawer	292mmH x 386mmW x 635mmD	



